

RECEIVED BY

JAN 11 1985

O. C. D.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

P. O. Box 2760, Midland, Tx 79702-2760

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 250' FNL & 1600' FWL unit Letter C.

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☒

(other)

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☐☐5. LEASE
NM-06792

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
BIG EDDY UNIT8. FARM OR LEASE NAME
BIG EDDY UNIT9. WELL NO.
9110. FIELD OR WILDCAT NAME
WILDCAT- MORROW11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 5 T21S, R30E12. COUNTY OR PARISH
EDDY13. STATE
NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3544.6' GL, 3565.6' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Preparing to P & A. Called Bob Pitschke for plugging orders.
(BLM)200' Plug @ 12,500' T/Morrow, 200' Plug @ T/Atoka @ 12,100' 200'
Plug @ T/Cisco (Penn), 200' Plug @ T/Wolfcamp @ 10,500' using Class
"H" Neat 1.18 ft. 3/sx & 15.6#/Gal.+ .02% WR-2 .

150' Plug @ Bone Springs sand @ 7,500', 150' Plug @ 5,600;

50' in & 50' out @ 3828' 9-5/8" shoe, 50' in & 50' out @ 2,030'

13-3/8" Shoe, 50' in & 50' out @ 800' 20" Shoe, 50' @ Surface using Class

"H" Cement. INstall Dry Hole Marker, & Clean Location.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. C. Hartschke

TITLE Sr. Prod. Clerk DATE 1-2-85

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE