

Dec. 1973

Artesia, N.M.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

P. O. Box 2760, Midland, Tx 79702-2760

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 250' FNL & 1600 FWL unit Letter C.

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE

NM -06792

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

BIG EDDY UNIT

8. FARM OR LEASE NAME

BIG EDDY UNIT

9. WELL NO.

91

10. FIELD OR WILDCAT NAME

WILDCAT - MORROW

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 5, T21S, R30E

12. COUNTY OR PARISH

Eddy New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3544.6' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Set plugs as follows; * Using Class "H" Neat w/1.18 ft. 3/sx-15.6 #/gal.+ .02% WR-2.

- * 12,350'-12,550' 80 sx Class "H" Neat T/Morrow
- * 11,714'-11,914' 80 sx Class "H" Neat T/Atoka
- * 11,350'-11,550' 80 sx Class "H" Neat T/Cisco (Penn)
- * 10,365'-10,565' 80 sx Class "H" Neat T/Wolfcamp
- 7,250'- 7,400' 75 sx Class "H" Neat T/BoneSprings
- 5,525'- 5,675' 75 sx Class "H" Neat
- 3,778'- 3,878' 50 sx Class "H" Neat 9-5/8" Shoe
- 1,960'- 2,060' 50 sx Class "H" Neat 13-3/8" Shoe
- 750'- 850' 50 sx Class "H" Neat 20" Shoe

Surface used 10 sx Class "H" Neat, Install dry hole marker. Released Rig at 2:00 P.M. 1-3-85. Plugging was witnessed by Russ Hayworth, with MCC. Well P&A Jan. 3, 1985- FINAL REPORT.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *R.C. Hadlock*

TITLE *Sec. Prod. Clerk*

DATE *Jan. 4, 1985*

(This space for Federal or State office use)

APPROVED BY *Don M. Lawrence*
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

1-28-86