

RECEIVED BY

Form 3100-5  
November 1983 NM  
Formerly 9-331

JAN 3 1985

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-46275

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

---

7. UNIT AGREEMENT NAME

---

8. FARM OR LEASE NAME

Burton Flat E Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat E. H. H. B.S.

11. SEC., T., R., M., OR BLM. AND  
SURVEY OR AREA

Sec. 1 - T21S - R27E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3200' GR

12. COUNTY OR PARISH

Eddy

13. STATE

NM

18.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other) Monthly Report

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☐

REPAIRING WELL

☐  
☐  
☐  
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

11-9-84 Spud 17-1/2" hole @ 0300 hrs.

11-11-84 Drlg. @ 840' in sandstone, shale, dolomite. Set 21 jts. 13-3/8", 68#, K55 csg. @ 840'. Cement w/ 700 sx Pacesetter light and 200 sx ClC. Circ. 96 sx to pit. Test csg. to 1000 psi for 30 min. Held OK. WOC approximately 64 hrs. before drill out.

11-19-84 Drlg. @ 2590' in 12-1/4" hole. Set 64 jts., 8-5/8", 24#, K55 csg. @ 2584'. Cement w/ 1475 sx ClC. Circ. 731 sx to surface. Test csg. to 1250 psi for 30 min. Held OK. WOC approximately 37 hrs. before drill out.

11-30-84 Drlg. @ 5597' in 7-7/8" hole. Logged.

12-1-84 Set 141 jts. 5-1/2", 14, 15.5, K55 csg. @ 5592, DV tool @ 3392'. Cement w/ 610 sx ClC and 620 sx TLW. Circ. 5 sx to surface. FRR @ 0400 hrs. Test csg. to 2000 psi for 30 min. Held OK. WOC approximately 48 hrs. before beginning completion operation.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Melba Kriplinger*

TITLE

Unit Head

DATE

12-21-84

(This space for Federal or State office use)

APPROVED BY

*SWQ*

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAN 2 1985

*Carroll*

NEW MEXICO

\*See Instructions on Reverse Side