

RECEIVED BY

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

JUN 04 1985

SUNDAY NOTICES AND REPORTS ON WELLS

Use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. O. C. D.

OIL GAS
ARTESIA, OFFICE

OTHER Drilling

2. NAME OF OPERATOR

Liberty Oil & Gas Corporation

3. ADDRESS OF OPERATOR

P.O. Drawer 810, New Roads, Louisiana 70760

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1980' FSL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3197' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM-40256

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

H.W. Stott Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Avalon East-Bone Spring

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1, T21S, R27E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

Casing & Cement

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Surface & Intermediate Casing & Cement

4/27/85 Spud 17 1/2" hole @ 3:00 P.M.

4/28/85 T.D. 419'. Ran 13 joints, 13 3/8", 54.5#, K-55, ST&C casing and set
@ 419'. Cemented with 400 sx Class 'C', 2% CaCl. Circulated 38 sx
to surface. W.O.C. 12 hours. Pressure tested casing 500 p.s.i. for
30 minutes.

5/03/85 T.D. 2550'.
Ran 60 joints 8 5/8", 24.0#, J-55, ST&C casing and set @ 2550'.
Cemented with 200 sx Class 'C' Thixset followed by 1000 sx Hal-lite,
tailed in with 200 sx Class 'C'. Circulated 285 sx to surface.
W.O.C. 12 hours. Pressure tested casing 1000 p.s.i. for 30 minutes

18. I hereby certify that the foregoing is true and correct

SIGNED

Henry W. Franklin

TITLE

Agent

DATE

May 21, 1985

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL

ACCEPTED FOR RECORD

Mr. Q

MAY 31 1985 *See Instructions on Reverse Side