

H. W. Stott Fed. #1  
East Avalon Field  
Eddy County, New Mexico

Present Condition of Hole

T.D. 5615 ft.            K. B. 12.5 ft to ground  
13-3/8" 72# K-55 cmtd at 419 ft.  
8-5/8" 24# J-55 cmtd at 2550 ft.  
5-1/2" 15.5# J-55 cmtd at 5615 ft.

D.V. Tool at 3202 ft.  
Perf'd 5504-5511, 5514-5526 ft.  
2-3/8" tbg landed at 5544 ft.

Recompletion Procedure

1. Move in workover rig. Fill hole with lease salt water. Install BOP. Pull rods, pump and tubing.
2. Rig up wire-line. Run gauge ring to 5480 ft. Run and set cast iron bridge plug at 5450 and cap with 20 ft of cement using dump bailer.
3. Jet perforate as follows at 4 HPF using casing gun and premium charges:  
2954-2968 ft.  
2990-3000 ft.  
3008-3016 ft.
4. Run in hole with treating packer on tubing and stimulate zones as per attached proposal.
5. Swab and/or flow test well.
6. Kill well and POH with tubing.
7. Rig up wire-line. Jet perforate 2750-2765 ft at 4 HPF using a casing gun with premium charges.
8. Run treating packer with retrievable bridge plug. Set bridge plug at 2900 ft. Pull up to 2850 ft and test bridge plug to 2500 psi.
9. Stimulate zone as per attached proposal.
10. Swab and/or flow test well.
11. Kill well and retrieve bridge plug.
12. Run tubing, rods and pump and place well on production.