

NEW MEXICO OIL CONSERVATION BOARD
DRAWER 107
ARTEZIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator		Lease		Well #	
MONSANTO OIL CO.		BURTON FLAT DA LT.		38	
Location of Well	Unit	Section	Township	Range	County
	X	2	21	27	Eddy
Drilling Contractor	Type of Equipment				
	NA		ROTARY		

* = CSG. TO WITNESS

APPROVED CASING RECORD

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2"	13 3/8"	48.0	NEW	600	CIRC
* 12 1/4"	8 5/8"	24.0	"	2500	CIRC
5 1/2"	5 1/2"	15.5	"	3700	750

Casing Data:

Surface joints of 8 5/8" inch 24-32" Grade K-55
☒ Approved ☐ (Rejected)
 Inspected by M.S. date 9/2/86

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____
 Type of Shoe used guide Float collar used insert Joints welded yes
 TD of hole 2640' Set 2640' Feet of 8 5/8" inch 24-32" Grade K-55
☒ New-used csg. @ 2640' with 200 220cc sacks neat cement around shoe
 - 200 sax ThixoLite additives (6#/sx Hiseal)
 Plug down @ 11:30 ☒ (AM) (PM) Date 9/4/86
 Cement circulated yes No. of Sacks 75 sx
 Cemented by Western Co. Witnessed by Mike Stullfield
 Temp. Survey ran @ _____ (AM) (PM) Date _____ Top cement @ _____
 Casing test @ _____ (AM) (PM) Date _____
 Method Used _____ Witnessed by _____
 Checked for shut off @ _____ (AM) (PM) Date _____
 Method used _____ Witnessed by _____
 Remarks: + 1200 sx pacesetter Lite "C" (6#/sx Hiseal, 4% gel.)

10 centralizers on 1st 21 ft

lost circ. + required 2015'