

Form 3160-5 (November 1983)  
(Formerly O-3160)

UNIT STATES

SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

2/57

RECEIVED BY

BUREAU OF LAND MANAGEMENT

# SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☒ O. C. D.  
OIL ☐ GAS ☐ OTHER  
WATER ☐ WELL ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

990 FSL & 1930 FEL, Sec. 21-T21S-R28E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3211' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 0486

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Big Eddy Unit

8. FARM OR LEASE NAME

Big Eddy Unit

9. WELL NO.

109

10. FIELD AND POOL, OR WILDCAT

Undes. Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR ARMA

Unit 0, Sec. 21-21S-28E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Spudded 12-1/4" hole 9:15 AM 3-10-85. Ran 10 joints 8-5/8" 24# J-55 set 426'. 1-Texas Pattern Notched guide shoe set 426'. Insert float set 384'. Cemented w/125 sx Pacesetter Lite w/3% CaCl2 and 1/4#/sx celloseal. Tailed in w/100 sx Class "C" w/2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 6:55 PM 3-10-85. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 85 sx to pit. WOC. Drilled out 6:00 PM 3-11-85. WOC 23 hrs and 5 mins. Nipped up and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED Juanita Goodlett

TITLE Production Supervisor

DATE 3-13-85

(This space for Federal or State office use)

APPROVED BY [Signature]  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

MAR 18 1985

\*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.