

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TR.
(Other Instructions
on reverse side)

DATE
D re

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-4987

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "12"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Fenton Delaware, N.W.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 12-T42S-R27E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

J. M. Huber Corporation

3. ADDRESS OF OPERATOR

7120 I-40 West, Suite 232, Amarillo, Texas 79106

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)

At surface

2310' FSL & 990' FEL of Section 12

14. PERMIT NO.

30-015-25288

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

3183.3' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Starting date: December 18, 1987

Finishing Date: December 22, 1987

1. Spot 45 sx Class "H" cmt with 2% CaCl from 3170-2930'. Displaced wellbore w/10.5 lb/gal gelled brine. Tag TOC @ 2930'.
 2. Spot 10 sx Class "H" cmt inside 5-1/2" casing from 2930-2842'.
 3. Spot 20 sx Class "H" cmt inside 5-1/2" casing from 2565-2389'. Tag TOC @ 2410'.
 4. Shot 5-1/2" casing @ 1680'. Pulled 1682' 5-1/2" casing.
 5. Spot 50 sx Class "H" cement over casing stub 1565-1730'.
 6. Spot 50 sx Class "H" cement inside 8-5/8" casing from 510-345'.
 7. Spot 20 sx Class "H" cement inside 8-5/8" casing from 50' to surface.
 8. Cut off 8-5/8" casing 3' BGL, welded cap, and installed marker as per BLM regulations. Filled pits, cleared and leveled location. Will rip road and pad shortly weather permitting. Road & location will be reseeded in spring.
- Note: Loaded hole with 10.5# gelled brine between all plugs.

Plugging procedure per Peter Chester w/BLM in Roswell, New Mexico.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert R. Glenn
Robert R. Glenn

TITLE Dist. Production Manager

DATE 12-22-87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

COPIES FOR RECORD

DEC 22 1987

SJS

*See Instructions on Reverse Side