

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Form approved.
Budget Bureau No. 1004-0-1
Expires August 31, 1985.

215F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR

Mewbourne Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 7698, Tyler, Texas 75711

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.
At surface

660' FNL & 660' FWL

RECEIVED BY

001 21 1985

O. C. D.

ARTESIA OFFICE

5. LEASE DESIGNATION AND SERIAL NO.

NM-59011

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "J" Comm.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Rocky Arroyo Wolfcamp

South Gas Pool

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

29-22S-22E

14. PERMIT NO.

API # 30-015-25410

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4561.4 GL

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Setting Intermediate Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/9/85 - Ran guide shoe, 39' shoe joint, float collar, 5 centralizers, 14 joints 8-5/8" 24# J-55 ST&C (517') 23 joints 8-5/8" 32# J-55 ST&C (942'). Total of 1459' set at 1448'. Halliburton cemented with 1000 gals. of Flocheck 21 and 100 sxs of thick set, 525 sxs of Econolite with 12# gilsonite, 1/4# flocele, 6# salt and 200 sxs Class C with 2% CaCl, 1/4# flocele. PD to 1409' at 4:15 A.M. Circulated to surface.

ACCEPTED FOR RECORD

001 21 1985

CARLSBAD, N.E. MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Exploration Secretary

DATE Oct. 17, 1985

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side