

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

RECEIVED BY BOX 2088
SANTA FE, NEW MEXICO 87501

MAY 02 1986

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Ray Westall	8. Farm or Lease Name Baseball Park
3. Address of Operator P.O. Box 4 Loco Hills, New Mexico 88255	9. Well No. 3
4. Location of Well UNIT LETTER K 2104 FEET FROM THE South LINE AND 2218 FEET FROM THE West LINE, SECTION 24 TOWNSHIP 22S RANGE 26E NMPM.	10. Field and Pool, or Windcat Und. S. Carlsbad Delaware
15. Elevation (Show whether DF, RT, GR, etc.) 3177. GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER Spud, 8 5/8", TD, 5 1/2"	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-14-86 Spud 12 1/4" hole @ 8:00 P.M.

4-15-86 Ran 13 jts. 412' of 8 5/8" 24# J-55 casing. Cemented @ 425' w/250 sxs Class "C" 2% CaCl₂, 1/4# Cello-seal-did not circulate. Redi-mix w/2 yds. cement. Plug down 11:30 A.M. WOC & redi-mix. Nipple up BOP & test, 1040" for 30 min. held 18 hr.

4-23-86 T.D. 4520'. Ran 110 jts. 4538.53' 17# 5 1/2" casing. Set & cemented @ 4520' w/590 sxs P.S. Lite "C", 8# salt + 4# sx Hiseal, 2% AFS, 335 sxs 50-50 Poz C + 5# salt 1/4# sx Cello-seal. Plug down @ 2:55 P.M. 4-24-86

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ray Westall TITLE Operator DATE 4-30-86

APPROVED BY Mike Williams TITLE Oil & Gas Inspector DATE MAY 9 1986

CONDITIONS OF APPROVAL, IF ANY: