PR OF CORS. CONTINUE Form approved. Budget Bureau No. 1004-c. Scrm 3160-5 . (i UN ED STATES SUBMIT IN TRIP Expires August 31, 1985 (Nowember 1983) DEPARTMEN. OF THE THTERIOR CONTROL lustruction 5. LEASE DESIGNATION AND BERIAL S. (Formerly 9-331) NM-25348 BUREAU OF LAND MANAGEMENT RECEIVED 6 IF INDIAN, ALLOTTEE OR THIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 10 41 AN 188 IT AGREEMENT NAME GAS W**e**ll WELL X OTHER CAR 8 FARM OR LEASE NAME NAME OF OPERATOR AREA ( ) INDREX, Pederal 10 ADDRESS OF OPERATOR S. WBLL NO. RECEIVED 74133 7633 E. 63rd Place, Suite 500, Tulsa, Okla. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface 10. FIELD AND POOL OR WILDCAT Wildcat OCT 24'88 11. SEC., T., B., M., OR BLE. AND SURVEY OR AREA 635' FSL & 1980' FWL Sec 10, T-22-S,R-25-E Q. C. D. 15 ELEVATIONS (Show whether DF, RT, GR, etc.) ARIESIA, OFFICE 14. PERMIT NO 12. COUNTY OR PARISH | 13. STATE 3495.6' GL Eddy New Mexico 16 Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO SUBSEQUENT REPORT OF : TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF FRACTURE TREAT PRACTURE TREATMENT ALTERING CASING SHOOT OR ACIDIZE ABANDON\* SHOOTING OR ACIDIZING (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETE: OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertiproposed work. If nent to this work.) 8-28-87 Spudded 17-1/2" hole @ 8:00 p.m. TD 17-1/2" hole to 560' @ 3:00 p.m. 8-30-87 Set 12 jts 13-3/8" J-55 casing @ 465'. Cemented w/200 sx C1 C w/5# Hi-seal 9-1-87 & 2% CaCl, mixed @ 14.8 ppg. followed by 175 sx C1 C w/2% CaCl, mixed @ 14.8 ppg. CIP @ 11:30 a.m. 9-1-87 & circ 40 sx cmt to surface. 9-2-87 Drill 12-1/4" hole below 13-3/8" csg. TD 12-1/4" hole to 1855' @ 5:45 p.m. Set 48 jts 8-5/8" 24# ST&C csg @ 1848'. 9-4-87 Cemented w/450 sx Cl C cont 12% thickset mixed @ 14.8 ppg. followed by 100 sx C1 C cont 2% CaCl, mixed @ 14.8 ppg. CIP @ 11:00 p.m. No cmt to surface. Cmt'd 8-5/8" x 12-1/4" annulus through 1" tbg from 568' to surface with 9-5-87 175 sx C1 C cont 12% thickset mixed @ 14.8 ppg in 3 stages. Install 10" 3000 psi double hyd BOP & test to 2000 psi. Drill 7-7/8" hole 9-6-87 below 8-5/8" csg. CONTINUED ON ATTACHED PAGE. 18. I hereby certify that the foregoing is true and correct Agent for INDREX, Inc. SIGNED

## \*See Instructions on Reverse Side

TITLE

DATE \_16 25 38

(This space for Federal or State office use)

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY \_\_\_\_