

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☒ gas well ☐ other ☐ NOV 10 '87
2. NAME OF OPERATOR  
BASS ENTERPRISES PRODUCTION CO. PETROL. OFFICE
3. ADDRESS OF OPERATOR  
P.O. BOX 2760, MIDLAND, TEXAS 79702-2760
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 460' FSL & 330' FWK of Unit Letter U.  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Same as above
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- | REQUEST FOR APPROVAL TO:                      | SUBSEQUENT REPORT OF:               |
|-----------------------------------------------|-------------------------------------|
| TEST WATER SHUT-OFF <input type="checkbox"/>  | <input type="checkbox"/>            |
| FRACTURE TREAT <input type="checkbox"/>       | <input type="checkbox"/>            |
| SHOOT OR ACIDIZE <input type="checkbox"/>     | <input type="checkbox"/>            |
| REPAIR WELL <input type="checkbox"/>          | <input type="checkbox"/>            |
| PULL OR ALTER CASING <input type="checkbox"/> | <input type="checkbox"/>            |
| MULTIPLE COMPLETE <input type="checkbox"/>    | <input type="checkbox"/>            |
| CHANGE ZONES <input type="checkbox"/>         | <input type="checkbox"/>            |
| ABANDON* <input type="checkbox"/>             | <input checked="" type="checkbox"/> |
| (other) <input type="checkbox"/>              | <input type="checkbox"/>            |

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plug No.1 30 sx cement 582'-582'<sup>SSS</sup> Across top of Bone Spring.  
Plug No.2 30 sx cement 2775'-2675' Across intermediate CSG. shoe.  
Run in and tagged cement @ 2675' Per BLM orders.  
Plug No.3 30 sx cement 650'-550' opposite 13-3/8" surface CSG. shoe.  
Set 15 sx cement @ surface, Rig released @ 6:00 AM 11-4-87, install dry hole marker, clean up around location.  
Well plugged & abandoned 11-4-87.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R.C. Houtchens TITLE Sr. Prod. Clerk DATE November 5, 1987

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

Post ID-2  
1-8-88  
P&A

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment, data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.