

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88810
Budget Bureau No. 1004-0135
Expires: March 31, 1993

457

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company

3. Address and Telephone No.

P.O. Box 5270 Hobbs, New Mexico 88241

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FWL & 467' FSL
Sec. 6-T22S-R26E

5. Lease Designation and Serial No.

NM-7152

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Federal "N" #1

9. API Well No.

10. Field and Pool, or Exploratory Area

Hackberry Hills Atoka

11. County or Parish, State

Eddy Co., N.M.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☒ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other Squeeze & Perforate

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- Squeeze Canyon Perforations (9780' - 9808') with 160 'sx, Class "H" cement to 2500#
- Drill out and tested to 3,000#. Held ok
- Perforated Lower Morrow from 11,088'-11,395'. Acidized with 3000 gallons 7 1/2% HCL acid
- Tested and evaluate. Set 5-1/2" CIBP at 10,950'. Cap with 35' cement
- Perforated Atoka from 10,264'-10,272'
- Acidize Atoka with 1500 gallons 15% HCL acid
- Restore well to production

RECEIVED
MAR 29 10 30 AM '94
OIL
ADIT

6 10/10
SSS

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Engineer

Date March 21, 1994

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any

Title _____

Date _____