

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE  
OTHER INSTANCES  
Artesia, NM 88210

Budget Bureau No. 1004-0135  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-0556290

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Canter Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 10-T20S-R29E

12. COUNTY OR PARISH

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

GIL WELL ☐ GAS WELL ☒ OTHER Dry

2. NAME OF OPERATOR

J.C. Williamson

3. ADDRESS OF OPERATOR

P.O. Box 16 Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

330' FNL & 330' FEL

NOV 22 1993

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, RT, GR, etc.)

3309.5' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Perfs 4116-4125', 12 shots, Wireline Bridge Plug @ 3990', 30' cement on top.

Perfs 3696-3710', 12 shots, W.L. B.P. @ 3650', 30' cement on top.

Perfs 3199-3211', 12 shots, Well on pump.

50 sx on Perfs @ 3199-3211', tag cement. (set across shoe of 8 1/2" (sg @ 3200')

50 sx across shoe @ 1263', tag cement.

50 sx across shoe @ 250'.

50 sx @ surface, erect dry hole marker.

Cement annuli @ surface.

18. I hereby certify that the foregoing is true and correct.

SIGNED

George Kingree

TITLE

Engineer

DATE 10-18-93

(This space for Federal or State office use)

APPROVED BY

(ORIG. SGD.) JOE G. LARA

TITLE

Petroleum Engineer

DATE 11/18/93

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side