Form 3160-5 (June 1990)
Do not us

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS NM-81217 use this form for proposals to drill or to deepen or reentry to a different reservoir. 6. If Indian, Allottee or Tribe Name Use "APPLICATION FOR PERMIT - " for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well X Oil Well 8. Well Name and No. Bandaid Federal 2. Name of Operator Santa Fe Energy Resources, Inc. 9. API Well No. 3. Address and Telephone No. Unknown 3/)-015-550 W. Texas, Suite 1330, Midland, TX 79701915/687-3551 10. Field and Pool, or exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Indian Basin (Upper Penn) (C), 1294' FNL, & 2063' FWL, Sec. 5, T-22S, R-24E Assoc. 11. County or Parish, State Eddy CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION X Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Conversion to Injection Other <u>Temporarily Abandon</u> Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* We respectfully request a temporarily abandoned status for the subject well. This well will be temporarily abandoned as follows: If necessary kill well with 9 ppg mud. MIRU PU and NU BOP. Release packer and POH with tubing. RIH w/ gauge ring and set EZSV retainer at +7100'. RIH w/ tubing and sting in Mix and pump 150 sx Cl "C" cement. Sting out of retainer and pump 30' cement plug on top of retainer. POH and WOC. Tag plug. Load hole with 9 ppg mud. POH laying down tubing. MAY 1 7 1995 Install wellhead w/3 to 5 joints tubing for kill string and valve. OIL CON. DIV. This work is scheduled to begin on June 1, 1995. DIST. 2 Production Clerk Date May 15, 1995 (This space for Federal or State office use) Approved by Title Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction