

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Canyon
T. Salt	T. Strawn 10054
B. Salt	T. Atoka 10348
T. Yates	T. Miss
T. 7 Rivers	T. Devonian
T. Queen	T. Silurian
T. Grayburg	T. Montoya
T. San Andres	T. Simpson
T. Glorieta	T. McKee
T. Paddock	T. Ellenburger
T. Blinbry	T. Gr. Wash
T. Tubb	T. Delaware Sand 1700
T. Drinkard	T. Bone Springs 4860
T. Abo	T. 2nd Bone Springs 6326
T. Wolfcamp 8330	T. Morrow 11099
T. Penn	T. Lwr. Morrow 11400
T. Cisco (Bough C)	T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn. "B"
T. Kirtland-Fruitland	T. Penn. "C"
T. Pictured Cliffs	T. Penn. "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	531	531	Surface, Redbeds				
531	1000	469	Limestone				
1000	1540	540	LS,Dolo				
1540	1640	100	LS, Dolo, Anhy, Sd				
1640	1840	200	LS, Sd, Dolo				
1840	2000	160	LS				
2000	2360	360	LS, Sd, Sh				
2360	2644	284	LS, Sd, Dolo				
2644	3214	570	Sd, Sh				
3214	3340	126	Sd, Sh, Dolo				
3340	4822	1482	Sd, Sh				
4822	5844	1022	Sh, LS				
5844	6000	156	Sd, Sh, Lm				
6000	6380	380	Sh, Lm				
6380	6480	100	Lm, Sh, Sd				
6480	8060	1580	LS, Sh				
8060	8440	380	Sd, LS, Sh				
8440	10704	2264	Sh, LS				
10704	11650	946	Sh, LS, Sd				