

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN T. LICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-011
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-81606

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FEDERAL "Q"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Avalon Morrow

11. SEC., T., R., M., OR BLK. AND
28 SURVEY OR AREA

AND 20-T20S-R27E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

JAN - 8 '90

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Mewbourne Oil Company /

3. ADDRESS OF OPERATOR

P. O. Box 7698, Tyler, TEXAS 75711

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FWL & 990' FSL

14. PERMIT NO.

API #30-015-26246

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3218.1' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Intermediate Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.) *

12/08/89 - Ran 8-5/8", 24# & 32#, J-55 casing set at 2330', cemented
with 100 sxs Class "C" + 12% Thixad + 2% CaCl₂ followed by
900 sxs Pacsetter Lite Premium + 5#/sx Gilsonite + 1/2#/sx
Celloseal + 2% CaCl₂ followed by 200 sxs Class "C" + 5#/sx
Gilsonite + 1/2#/sx Celloseal. Plug down to 2295' at 1:25 AM
12/8/89. Circulated 50 sxs of cement. Float held OK.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engr. Oprns. Secretary

DATE

12/12/89

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side