Multi Point Surface Use and Operations Plan Oxy USA Inc.'s Government AB #5

Page 3

6. <u>Source of Construction Materials</u>

Caliche for surfacing the new access road and the well pad will be obtained from a Federal pit located in the Section 19, T-20-S, R-28-E, Eddy County, New Mexico. Archaeological clearance has been obtained for this pit.

- - ---

7. Method of Handling Waste Disposal

- A. Drill Cuttings will be disposed of in drilling pits.
- B. Drilling fluids will be allowed to evaporate in the drilling pits until pits are dry.
- C. Water produced during tests will be disposed of in the drilling pits. Oil produced during tests will be stored in test tanks until sold.
- D. Current laws and regulations pertaining to the disposal of human waste will be complied with.
- E. Trash, waste paper, garbage and junk will be buried in a separate trash pit and covered with a minimum of 24 inches of dirt. All waste material will be contained to prevent scattering by the wind. Location of the trash pit is shown on the wellsite layout. Exhibit "D".
- F. All trash and debris will be buried or removed from the wellsite within 30 days after finishing drilling and/or completion operations.
- 8. Ancillary Facilities
 - A. None needed.
- 9. <u>Wellsite Layout</u>
 - A. The location and dimensions of the well pad, mud pits, reserve pit and location of major rig components are shown on the well site layout sketch. The V-door will be to the east and the pits to the north. Exhibit "D".
 - B. Leveling of the wellsite will be required with cuts and fills of 2 to 3 feet.
 - C. The reserve pit will be plastic lined.