

Multi Point Surface Use and Operations Plan
Oxy USA Inc.'s Government AB #5

Page 2

- B. Surfacing material: Six inches of caliche and water, compacted and graded.
 - C. Maximum Grade: Less than 3%.
 - D. Turnouts: None needed
 - E. Drainage Design: New access road will have a drop of 6" from center line to each side.
 - F. Culverts: None needed
 - G. Cuts and Fills: Leveling the location and upgrading the road will require cuts and fills of 2 to 3 feet.
 - H. Gates or Cattleguards: None required
3. Existing wells within a one mile radius of the proposed development well are shown on Exhibit "C".
4. Location of Existing and/or Proposed Facilities
- A. If the well is productive, the tank battery and flowline will be located on the well pad and no additional surface disturbance will occur. The equipment will consist of two 300 bbl tanks and a production unit (stack pack). One of the tanks will be used to collect produced water which will be trucked to disposal. The other tank will be used to collect and store condensate produced from the well. All permanent above ground facilities will be painted in accordance with the BLM's painting guidelines simulating the color of sandstone brown.
 - B. All site security guidelines identified in 43 CFR 3162.7 regulations will be adhered to and a site security plan will be submitted for the Government AB #5 tank battery. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed.
5. Location and Type of Water Supply
- Fresh water will be used to drill this well. It will be purchased near Carlsbad, New Mexico and transported to the well site.