

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-26251

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

V-3014

7. Lease Name or Unit Agreement Name

Tomcat State

8. Well No.

1

9. Pool name or Wildcat

Und. Catclaw Draw Delaware

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

ELK OIL COMPANY

3. Address of Operator

Post Office Box 310, Roswell, New Mexico 88202-0310

4. Well Location

Unit Letter P : 760 Feet From The South Line and 320 Feet From The East Line

Section 16

Township 21S

Range 25E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3846' Gr

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud well on 01/12/90. Drilled 12 1/4" hole to 1600'. Ran 38 joints (1600') of 8 5/8", 24#, J-55 casing. Cemented with 100 sxs Thick Set with 1/2# flocele, 10# gilsonite, 3% CaCl; 500 sxs Hallilite containing 1/4 # flocele, 10# gilsonite, 2% CaCl; tailed by 250 sxs Class C containing 2% CaCl. Temperature survey shows cement top at 275'.

1st stage 1": Pickup 1" pipe and tag up at 283'. Pumped 50 sxs Class C containing 4% CaCl.

2nd stage 1": Pickup 1" pipe and tag up at 90'. Pumped 50 sxs Class C containing 4% CaCl.

3rd stage 1": Pickup 1" pipe and tag up at 10'. Pumped 35 sxs Class C containing 4% CaCl. Circulated 5 sxs.

WOC 18 hours. Tested to 1000#, test held okay. Prep to drill 7 7/8" hole.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

President

DATE 1/29/90

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT II

SUPERVISOR, DISTRICT II

FEB 2 1990

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY: