DEPARTMENT OF THE INILKIUK verse side) PURFALL (AND MANAGEMENT	NM0528964 25
SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
(Do not use this form for proposals to drill or to deepen or plug back to the Use "APPLICATION FOR PERMIT" for such proposals.)	7. UNIT AGREEMENT NAME
OIL CAS X OTHER	MAR 22'90 8. PARM OR LEASE NAME
NAME OF OPERATOR	Government W
OXY USA Inc. /	O. C. D. 9. WHILE NO.
	RIESIA, OFFICE 2
P.O. Box 50250 Midland, TX 79710 LOCATION OF WELL (Report location clearly and in accordance with any State requirement	10. FIELD AND POOL, OR WILDCAT
At surface	Burton Flat Wolfcamp, N. 11. SEC., T., B., M., OR BLE. AND BURNET OR ARBA
990 FSL 1980 FEL Sec 22 (SWSE) T20S R28E	Sec 22 T20S R28E
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 18. STATE
14. PERMIT NO. 3228 6 GR	Eddy NM
30-015-26253 Substitute of Notice Appropriate Box To Indicate Nature of Notice Nature Natu	ice. Report, or Other Data
1 .	BURSEQUENT REPORT OF:
NOTICE OF INTENTION TO:	PROPAIRING WELL
PULL OR ALTER CASING	BRUT-OFF
MULTIPLE COMPLETE	RE TREATMENT ABANDONMENTS
ABANDON*	Set casing & cement
REPAIR WELL CHANGE PLANS	OTE: Report results of multiple completion of the
proposed work. If well is directionally dilited and interest and inter	empletion or Recompletion months and some pertinent dates, including estimated date of starting angive pertinent dates, including estimated date of starting angive pertined and true vertical depths for all markers and somes pertined and true vertical depths for all markers and somes pertined and true vertical depths for all markers and somes pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers and some pertined and true vertical depths for all markers are vertical depths for all markers and true vertical depths for all markers are vert
TD-3000' Drill 12-1/4" hole to a T 5/8" 24#(56) & 32#(14) K55 casing & sx Cl C Lite w/ 3.25#/sx Celloflakes C w/ 2% CaCl2. Plug down @ 0530 MST capant to mit. WOC 18 hrs. Test 8-5/	TD of 3000'. Run 40 jts. 8- set @ 3000'. Cement w/ 1300
TD-3000' Drill 12-1/4" hole to a T 5/8" 24#(56) & 32#(14) K55 casing & sx Cl C Lite w/ 3.25#/sx Celloflakes	TD of 3000'. Run 40 jts. 8-set @ 3000'. Cement w/ 1300 & 5#/sx Gilsonite; 300 sx Cl 2/25/90. Circulated 489 sx /8" casing to 1000#, held OK.
TD-3000' Drill 12-1/4" hole to a T 5/8" 24#(56) & 32#(14) K55 casing & sx Cl C Lite w/ 3.25#/sx Celloflakes C w/ 2% CaCl2. Plug down @ 0530 MST cement to pit. WOC 18 hrs. Test 8-5/Drill ahead w/ 7-7/8" hole.	TD of 3000'. Run 40 jts. 8-set @ 3000'. Cement w/ 1300 & 5#/sx Gilsonite; 300 sx Cl 2/25/90. Circulated 489 sx /8" casing to 1000#, held OK.
TD-3000' Drill 12-1/4" hole to a T 5/8" 24#(56) & 32#(14) K55 casing & sx Cl C Lite w/ 3.25#/sx Celloflakes C w/ 2% CaCl2. Plug down @ 0530 MST cement to pit. Woc 18 hrs. Test 8-5/Drill ahead w/ 7-7/8" hole.	TD of 3000'. Run 40 jts. 8- set @ 3000'. Cement w/ 1300 & 5#/sx Gilsonite; 300 sx Cl 2/25/90. Circulated 489 sx /8" casing to 1000#, held OK.
TD-3000' Drill 12-1/4" hole to a T 5/8" 24#(56) & 32#(14) K55 casing & sx Cl C Lite w/ 3.25#/sx Celloflakes C w/ 2% CaCl2. Plug down @ 0530 MST cement to pit. Woc 18 hrs. Test 8-5/Drill ahead w/ 7-7/8" hole.	TD of 3000'. Run 40 jts. 8- set @ 3000'. Cement w/ 1300 & 5#/sx Gilsonite; 300 sx Cl 2/25/90. Circulated 489 sx /8" casing to 1000#, held OK.
TD-3000' Drill 12-1/4" hole to a T 5/8" 24#(56) & 32#(14) K55 casing & sx Cl C Lite w/ 3.25#/sx Celloflakes C w/ 2% CaCl2. Plug down @ 0530 MST cement to pit. WOC 18 hrs. Test 8-5/ Drill ahead w/ 7-7/8" hole. CARLEBAC	TD of 3000'. Run 40 jts. 8- set @ 3000'. Cement w/ 1300 & 5#/sx Gilsonite; 300 sx Cl 2/25/90. Circulated 489 sx /8" casing to 1000#, held OK.
TD-3000' Drill 12-1/4" hole to a T 5/8" 24#(56) & 32#(14) K55 casing & sx Cl C Lite w/ 3.25#/sx Celloflakes C w/ 2% CaCl2. Plug down @ 0530 MST cement to pit. WOC 18 hrs. Test 8-5/ Drill ahead w/ 7-7/8" hole. CARLEBAC	TD of 3000'. Run 40 jts. 8- set @ 3000'. Cement w/ 1300 & 5#/sx Gilsonite; 300 sx Cl 2/25/90. Circulated 489 sx /8" casing to 1000#, held OK.
TD-3000' Drill 12-1/4" hole to a To 5/8" 24#(56) & 32#(14) K55 casing & sx Cl C Lite w/ 3.25#/sx Celloflakes C w/ 2% CaCl2. Plug down @ 0530 MST cement to pit. WOC 18 hrs. Test 8-5/4 Drill ahead w/ 7-7/8" hole. CARESAC	TD of 3000'. Run 40 jts. 8- set @ 3000'. Cement w/ 1300 & 5#/sx Gilsonite; 300 sx Cl 2/25/90. Circulated 489 sx /8" casing to 1000#, held OK.

*See Instructions on Reverse Side