

SUPPLEMENTAL DRILLING DATA

TXO PRODUCTION CORP.

WELL NO. 1 BURTON FLAT FEDERAL

1. WELL LOCATION RELATIVE TO POTASH RESERVES:

A plat is attached showing surface and bottom-hole locations of the proposed well. Also shown is the surface location relative to the nearest potash lessee's designated boundary of life-of-mine potash reserves.

2. DIRECTIONAL DRILLING:

The proposed well will be vertically drilled from the surface to the kick-off point at a depth of about 5200 feet. A plat is attached depicting deviation of the proposed well calculated to bottom the well in the Strawn oil zone 1725 feet south of the surface location.

3. ESTIMATED TOPS OF GEOLOGIC MARKERS:

Delaware	3175'
Bone Springs	6100'
Dean	8975'
Wolfcamp	9375'
Strawn	10,525'

4. ANTICIPATED POSSIBLE HYDROCARBON BEARING ZONES:

Strawn Oil

5. PROPOSED CASING AND CEMENTING PROGRAM:

CASING SIZE	SETTING DEPTH		WEIGHT	GRADE	JOINT
	FROM	TO			
20"	0	450'	94#	H-40	STC
13-3/8"	0	1500'	48#	H-40	STC
8-5/8"	0	2400'	24#	K-55	STC
"	2400'	3100'	24#	S-80	STC
4-1/2"	0	10,000'	11.6#	N-80	LTC
"	10,000'	11,000'	11.6#	S-95	LTC

Above depths are TVD.

20" casing to be cemented with approximately 500 sacks of Class "C" cement. Cement to circulate.