

SUNDRY NOTICES AND REPORTS ON WELLS

(This form is to be used for proposals to drill or to deepen or plug back to a Federal reservoir.
See APPLICATION FOR PERMIT--for such proposals.)

U. S. DEPARTMENT OF THE INTERIOR

NM-82853

RECEIVED

1. DATE OF RECEIPT DATE

2. NAME OF OPERATOR

Siete Oil and Gas Corporation

FEB 20 1991

3. NAME OF FEDERAL RESERVE

Blackfoot Federal

ADDRESS OF OPERATOR

P.O. Box 2523, Roswell, NM 88202-2523

O. C. D.
ARTESIA, OFFICE

4. WELL NO.

1

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 11 below.)2460' FNL & 330' FWL, SW $\frac{1}{4}$ NW $\frac{1}{4}$, Unit Letter D5. FORM AND FOOT. OR WILDCAT
Wildcat6. SEC. T. R. S. OR B.L. AND
QUAD. OR AREA

Sec. 17, T22S, R25E

7. NUMBER OF

8. ELEVATIONS (Show whether in ft. or m.)

3828 GR

9. COUNTY OR PARISH

Eddy

10. STATE

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER DRIFT-OUT

FRACURE TEST

SHOOT OR ACIDIZE

DETAILED WELL

(Other)

FILL OR ALTER CASING

MULTIPLE COMPLETES

ABANDON*

CHANGE PLANE

WATER DRIFT-OUT

FRACURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing & 1"(Note: Report results of multiple completions on Well
Completion or Abandonment Report and Log form.)

DETAILED WELL

ALTERING CASING

ABANDONMENT*

DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
drilling work. If well is directionally drilled, give orientation, bearings and measured and true vertical depths for all markers and given parts
completed work.) L&M Rig #2 spudded 17 $\frac{1}{2}$ " hole @ 12:00 noon.1/23/91 Drilled to 400' & TD 17 $\frac{1}{2}$ " hole @ 6:30 PM, RU & ran 10 jts (411') 61#
J-55 13 3/8" csg, set @ 400' w/100 sxs 35/65 POZA, 3% CaCl 15# hi-
seal, tail-in w/250 sxs CC, 2% CaCl, $\frac{1}{4}$ # D-29, did not circ, PD @
10:15 PM.1/24/91 Tagged cmt @ 297', cmt'd w/25 sxs CC, 4% CaCl, tagged cmt @ 249' &
cmt'd w/25 sxs CC w/4% CaCl, tagged cmt @ 244' & cmt'd w/25 sxs CC
w/4% CaCl, tagged cmt @ 232' & cmt'd w/50 sxs CC w/4% CaCl, tagged
cmt @ 242' & cmt'd w/75 sxs CC w/4% CaCl, tagged cmt @ 237' & cmt'd
w/25 sxs CC w/4% CaCl, tagged cmt @ 237' & cmt'd w/25 sxs CC w/4%
CaCl, tagged cmt @ 237' & cmt'd w/25 sxs CC w/4% CaCl, tagged cmt @
192' & cmt'd w/200 sxs 35/64 POZA, $\frac{1}{4}$ # D-29, 3% CaCl.1/25/91 Tagged cmt @ 153' & cmt'd w/25 sxs CC w/4% CaCl, tagged @ 246' &
cmt'd w/60 sxs CC w/5% CaCl & 1.5% aquafix, tagged @ 245' & cmt'd
w/50 sxs CC w/4% CaCl, tagged @ 189' & cmt'd w/50 sxs CC w/5% CaCl,
tagged @ 157' & cmt'd w/50 sxs CC w/5% CaCl, tagged @ 156' & cmt'd
w/25 sxs blast sand, tagged @ 154' & cmt'd w/10 sxs blast sand,
tagged @ 152' & cmt'd w/50 sxs CC, 5% CaCl & 1.5% aquafix, tagged @
126' & cmt'd w/50 sxs CC w/5% CaCl, tagged @ 126' & cmt'd w/50 sxs
CC w/5% CaCl & 1.5% aquafix.1/26/91 Tagged @ 123' & cmt'd w/6 yards chat & 25 sxs CC w/5% CaCl, tagged
@ 96' & cmt'd w/60 sxs CC w/6% CaCl, cmt to surface, top out w/25 sxs
CC w/4% CaCl, PD @ 1:30 PM, resumed drlg.

All BOP & test to 1000#, held ok.

I hereby certify that the foregoing is true and correct

SIGNED Cathy Bartley-GeelyTITLE Drilling TechnicianDATE 2/5/91

(This space for Federal or State official use)

APPROVED BY _____
CONDITIONS OF APPROVAL IF ANY:

TITLE _____

DATE FOR RECORD _____