2	UNIT STATES ARTMENT JE THE INTE SUREAU OF LAND MANAGEME	- 6	Form approve Budget Burca Expires Augu 5. LEASE DESIGNATI NMNM82993	AU No. 1004-0135 ast 31, 1985 ON AND BRIAL NO. C	
(Do not use this form for	NOTICES AND REPORTS r proporais to drill or to deepen or plu pplication FOR PERMIT—" for suc	in back to a different stable			
OIL GAB WELL O	(TH ZR	SEP 11 IN MOR	7. UNIT AGREEMENT	NAME	
2. NAME OF OPERATOR	USA Inc.	CLIC SEP 19	'90 8. PARM OR LEADE ?		
3. ADDRESS OF OPERATOR P.O. BOX 5025	D. WELL NO. 2	2			
 LOCATION OF WELL (Report location clearly and in accordance with any State requirements." See also space 17 below.) At surface 1980 FNL 1980 FWL Sec 22 (SENW) T20S R28E 			Burton Flat	10. FIELD AND POOL, OR WILDCAT Burton Flat Morrow 11. SBC., T., R., M., OR BLE, AND SUBPER OR ANA	
			Sec 22 T20S		
14. FERMIT NO. 3001526402	15 ELEVATIONS (Show whether 3227.2'		12. COUNTY OR PART Eddy	SH 13. STATE NM	
	ck Appropriate Box To Indicate		or Other Data		
TEST WATER SHUT-OFF FRACTURE TREAT RHOOT OR ACIDIZE REPAIR WELL (Other)	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON® CHANGE PLANS	WATEB SHUT-OFF FBACTUBE TREATMENT SHOOTING OR ACIDIZING (Other) <u>Set casi</u> (Note: Report res (Completion or Reco	BEQUENT REPORT OF: BEFAIRING ALTERING ALTERING ABANDONS ING & CEMENT Ults of multiple completion pupietion Report and Log	CASING AENT• D OD Well	
17. DESCRIBE PROPOSED OR COMPLE proposed work. If well is nent to this work.)*	TED OPERATIONS (Clearly state all yearth directionally drilled, give subsurface lo	and the second			

Drill 12-1/4" hole to a TD of 3000'. RIH w/ 9-5/8" (15jts-40# & 57jts-36#) K55 casing, set @ 3000'. Cement as follows w/ 300sx Cl H cmt w/ 1% CaCl2, 1/4#/sx celloseal, 10% Thixad, & 10#/sx gel, 1350sx Pacesetter lite w/ 5#/sx Gil, 1/4#/sx celloseal, tailing w/ 300sx Cl C cmt w/ 2% CaCl2. Plug down @ 0430hrs CDT 8/24/90. Circ 200sx cmt to pit. BLM notified but did not witness. WOC 12hrs, set slips. NUWH test to 1200#, held OK. NUBOP, Rams, & Choke manifold test to 5000# & Hydril to 3000#, held OK. Drill out float collar & shoe, test csg to 2500#, held OK. Resume drilling 8-3/4" hole w/ full circ.

	Note	n de la companya de l La companya de la comp	
	ć		
18. I hereby certify that the foregoing is true and correct SIGNED			
(This space for Federal or State office use)	TITLE Production Accountant	DATE	
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE	

*See Instructions on Reverse Side