

the rig crews. This will be properly maintained during the drilling operations and removed upon completion of the well.

5. Chemicals remaining after completion of the well will be stored in the manufacturers containers and picked up by the supplier.

- B. Remaining drilling fluids will be allowed to evaporate in the reserve pit until the pit is dry enough for backfilling. In the event drilling fluids will not evaporate in a reasonable period of time they will be transported by tank truck to a state approved disposal site. Water produced during testing of the well will be disposed of in the reserve pit. Oil produced during testing of the well will be stored in test tanks until sold and hauled from the site.

8. ANCILLARY FACILITIES

No camps or airstrips will be constructed.

9. WELL SITE LAYOUT

- A. Exhibit "B" (Scale 1" = 50') shows the proposed well site layout.
- B. This exhibit indicates proposed location of reserve and trash pits.
- C. Mud pits in the active circulating system will be lined earthen pits. The reserve pit will also be lined with a PVC or polyethylene liner. The pit liner will be 6 mils thick. Pit liner will extend a minimum, 2'00" over the reserve pits dikes where the liner will be anchored down.
- E. The reserve pit will be fenced on three sides with four strands of barbed wire during drilling and completion phases. The fourth side will be fenced after all drilling operations have ceased. If the well is a producer, the reserve pit fence will be torn down. The reserve pit and those areas of the location not essential to production facilities will be reclaimed and seeded per BLM requirements.