	Į	Y.		151
. •	:			, <i>C</i> ()
Form 3160-5 (June 1990)	DEPARTMEN	TED STATES IT OF THE INTERIOR LAND MANAGEMENT	RECEIVED	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No.
Do not use thi	SUNDRY NOTICES AND REPORTS ON WELLS form for proposals to drill or to deepen or reentry to a different reservoir, Use "APPLICATION FOR PERMIT-" for such proposals			
	SUBMIT	7. If Unit or CA, Agreement Designation		
	MAR 2 8 1991			8. Well Name and No.
2. Name of Operator Mewbourne 3. Address and Teleph				Federal "Z" Com #1
P. O. Bo	7698, Tyler, Texas 75711 otage, Sec., T., R., M., or Survey Description)			30-015-26479 10. Field and Pool, or Exploratory Area
	otage, Sec., T., R., M., or Survey Description)       Avalon Morrow         & 660' FEL Section 29, T20S-R27E       II. County or Parish, State         Eddy			
I2. CHEC	K APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			
TYPE	DF SUBMISSION TYPE OF ACTION			
	ce of Intent	Abandonmer		Change of Plans New Construction
🗶 su	equent Report	Plugging Ba	ck	Non-Routine Fracturing
🗆 Fin	1 Abandonment Notice	Casing Repa		Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well
13 Describe Proposed e	Completed Operations (Clearly state al	I pertinent details, and give pertinent da	stes, including estimated date of starting	Completion or Recompletion Report and Log form ) g any proposed work. If well is directionally drilled,
give subsurface	locations and measured and true vertical depths for all markers and zones pertinent to this work.)*			
03/09/91 -	TD 10,730'. Ran 5-1/2" 17# & 20# N-80 LT&C Used casing. Set at 10,730'. Ran 2 centralizers around DV ttol. Cemented 1st stage with 915 sxs Class "H" w/5# KCL, .6 Halad-22A, .4 CFR-3, 6# Gilsonite ¼# Flocele. Good circulation. Displaced w/80 bbls KCL water + 150 bbls mud. PD at 6:15 AM. Opened DV tool and circulated hole for 6 hrs. Circulated 50 sxs cement off DV tool. Cemented 2nd stage with 1600 sxs HLC, 3# Gilsonite, ¼# Flocele, .5 Halad-22A, .3 CFR-3 + 100 sxs Class "H" Neat. Circulated 50 sxs cement to pit.			
03/21/91 -	1 - Ran cement bond log from PBTD at 10,662'. Showed good cement bond through all zones of interest. Ran 2-7/8" tubing set at 10,376'. Packer set at 10,362'.			
Th.	the tylegoing is true and correct	M. Int Engineerin	a Operations Search	toru 2/21/01
Signed (11)	rul or State office use)	The Largineer I	ig operacions secre	tary Date 3/21/91
Approved by	V	Title		Date
	-			
Title 18 U.S.C. Section or representations as to	001, makes it a crime for any person l ny matter within its jurisdiction.	enowingly and willfully to make to any	y department or agency of the United	States any fulse, fictitious or fraudulent statements
	*See Instruction on Reverse Side			