

SUPPLEMENTAL DRILLING DATA

FORTSON OIL COMPANY
SYLVITE FEDERAL NO. 1
1980' FNL & 660' FWL
Sec. 6, T20S, R30E
Eddy County, N.M.

The following information is filed in accordance with "Onshore Oil and Gas Order" No.s 1 & 2:

1. Geologic Name of Surface Formation: Permian age

2. Estimated Geological Marker Tops:

Rustler	320'	Wolfcamp	9600'
T/Salt	420'	Strawn	10560'
B/Salt	1300'	Atoka	10930'
Yates	1430'	Morrow	11550'
Seven Rivers	1530'	Lower Morrow	11900'
Delaware	3600'	Mississippian	12050'
Bone Spring	5950'	Barnett Shale	12500'

3. Estimated Depths to Water, Oil and Gas:

Water: above Rustler formation at 200'±
Oil : possibly in Delaware formation at 3600'±
Gas : possibly in Strawn and Morrow formation

4. Proposed Casing and Cement Program:

Surface Csg: 20", 94.0#, H-40, ST&C casing. Cement with 420 sx 35-65 pozmix followed by 400 sx Class 'A'. Circulated cement to surface.

First Inter: 13 3/8", 68.0#, J-55, LT&C casing. Cement with 1000 sx 35-65 pozmix followed by 200 sx of Class 'A'. Circulate cement to surface.

Second Inter: 8 5/8", 24 & 32.0#, J-55, LT&C casing. Cement with 1000 sx 35-65 pozmix followed by 300 sx of Class 'A' cement. Tie back into 13 3/8".

Prod. Casing: 5 1/2", 17, 20 and 23.0#, N-80 and S-95, LT&C casing. Cement with 1100 sx of Class 'H' cement followed by 500 sx of Class 'H' cement. Cement sufficient to cover top of Wolfcamp.