

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator	<u>DATES</u>	<u>Pst</u>	Lease	<u>Lost Tank "AIS" St</u>	Well #	<u>1</u>
Location of Well	Unit <u>I</u>	Section <u>36</u>	Township <u>21</u>	Range <u>31</u>	County <u>Eddy</u>	
Drilling Contractor	<u>Grace Drilling</u>			Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>54.5</u> #		<u>850</u>	<u>850 circ</u>
<u>12 1/4</u>	<u>8 5/8</u>	<u>32.0</u> #		<u>4500</u>	<u>2500 circ</u>
<u>7 7/8</u>	<u>4 1/2</u>	<u>17 + 20</u> #		<u>TD</u>	<u>AS warranted</u>

Casing Data:

Surface 20 joints of 13 3/8 inch 54.5 # Grade J-55(Approved) (Rejected)Inspected by WLO date 12/11/91

Cementing Program

Size of hole 17 1/2 Size of Casing 13 3/8 Sacks cement required 850 sxType of Shoe used guide Float collar used yes Btm 3 jts welded yesTD of hole 869 Set 874 Feet of 13 3/8 inch 54.5 # Grade J-55New used csg. @ 100 ^{Pck} 54.5 ^{cc} with 250 ^{cc} sacks neat cement around shoe
+ 250 ^{cc} sax additives 1/4 " sx cc SentPlug down @ 4:30 (AM) (PM) Date 12/12/91Cement circulated Yes No. of Sacks 175 sxs to pitCemented by Western Co. Witnessed by WLOTemp. Survey ran @ (AM) (PM) Date top cement @ Casing test @ (AM) (PM) Date Method Used Witnessed by Checked for shut off @ (AM) (PM) Date Method used Witnessed by

Remarks:

3 cent. used