Submit 3 Copies to Appropriate

State of New Mexico Energy, anerals and Natural Resources Department

Form C	103
Revised	1-1-89

District Office	
DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL (

P.O. Drawer DD, Artesia, NM 88210

TEMPORARILY ABANDON

PULL OR ALTER CASING

CONDITIONS OF APPROVAL, IF ANY:

OTHER:

CONSERVATION DIVISION

P.O. Box 2088 RECEIVED

Santa Fe, New Mexico 87504-2088

THE CA 1 1991

WELL API NO. 30-015-26584

5. Indicate Type of Lease

STATE X FEE

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	O. C. D.	6. State Oil & Gas Lease No. V-1673			
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name Lost Tank AIS State			
1. Type of Well: OIL GAS WELL X OTHER		nose fame into peace			
2. Name of Operator YATES PETROLEUM CORPORATION		8. Well No.			
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Pool name or Wildcat East Los Medanos Morrow			
4. Well Location Unit Letter I :1980 Feet From The South	Line and 660	Feet From The East Line			
Section 36 Township 21S		NMPM Eddy County			
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3612 GR					
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data					
NOTICE OF INTENTION TO:	SUB	SEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING			
TEMPORARII Y ARANDON CHANGE PLANS	COMMENCE DRILLING	OPNS. XX PLUG AND ABANDONMENT			

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 10:45 AM 12-7-91. Set 40' of 20" conductor. Cement to surface with readimix. Notified NMOCD, Artesia of spud. Resumed drilling $17\frac{1}{2}$ " hole 7:30 PM 12-10-91. Ran 20 joints 13-3/8" 54.5# J-55 casing set 869'. Guide shoe set 869', insert float set 828'. Cemented w/600 sx Pacesetter Lite + 2% CaCl2 + 1/4#/sx Celloseal (yield 1.76, wt 12.9). Tail in w/250 sx Class "C" + 2% CaCl + 1/4#/sx Celloseal (yield 1.32, wt 14.8). PD 4:15 AM 12-12-91. Bumped plug to 800 psi, released pressure and float held okay. Drilled out 5:30 AM 12-13-91. WOC 25 hours and 30 mins. NU and tested to 500 psi for 15 mins, OK. Reduced hole to 11" and resumed drilling.

OTHER:_

CASING TEST AND CEMENT JOB XX

I hereby certify that the inform	nation above is true and complete to the best of my knowled	dge and belief.	10 17 01
SIGNATURE	ita Dos allits	Production Supervisor	DATE
TYPE OR PRINT NAME	Juanita Goodlett		ТЕГЕРНОНЕ NO. 505/748-1471
(This space for State Use)	ORIGINAL SIGNED BY MIKE WILLIAMS SUPERVISOR, DISTRICT IT		DEC 2 0 1991
APPROVED BY	SUPERVISOR, DISTINGTON	mue	DATE