

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-26585

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V-1673

7. Lease Name or Unit Agreement Name

Lost Tank AIS State

8. Well No.
2

9. Pool name or Wildcat
Undes. Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

OCT 2 6 1991

2. Name of Operator

YATES PETROLEUM CORPORATION ✓

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter 0 : 660 Feet From The South Line and 1980 Feet From The East Line

Section 36

Township 21S

Range 31E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3579' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 8:30 AM 10-21-91. Set 40' of 20" conductor. Cement to surface with redi-mix. Notified Betty Rollins, NMOCD, Artesia, NM, of spud. Resumed drilling 17½" hole 3:45 PM 10-21-91. Ran 20 joints 13-3/8" 54.5# J-55 casing set 870'. Guide shoe set 870', float collar set 838'. Cemented w/600 sx Pacesetter Lite + 1/4#/sx Celloseal + 2% CaCl2 (yield 1.76, wt 12.0). Tailed in w/250 sx Class "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 4:30 PM 10-22-91. Bumped plug to 1000 psi, released pressure and float held okay. Circulated 100 sacks. WOC. Drilled out 10:30 AM 10-23-91. WOC 18 hours. NU and tested to 500 psi for 30 minutes, OK. Reduced hole to 11". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Production Supervisor DATE 10-24-91

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

OCT 26 1991

APPROVED BY

TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: