

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Yates Petr Corp</u>		Lease <u>Mary "AIV" St</u>		Well # <u>1</u>	
Location of Well	Unit <u>G</u>	Section <u>36</u>	Township <u>21</u>	Range <u>31</u>	County <u>Eddy</u>
Drilling Contractor	<u>Undesignated</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	54.4 #		850	850 Circ
12 1/4	* 8 5/8	32.0 #		4500	2500
7 7/8	5 1/2	17 + 20 #		TD	As Warranted

Casing Data:

inter
Surface 104 joints of 8 5/8 inch 32 # Grade J55
Stub (Approved) (Rejected)

Inspected by Stubblefield date 3-14-91

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 1800

Type of Shoe used Texas Float collar used yes Btm 3 jts welded yes

TD of hole 4480 Set 4511 Feet of 8 5/8 inch 32 # Grade J55

New-used csg. @ 4480 with 200 sacks neat cement around shoe
+ 1600 sack Pacesetter additives salt saturated

Plug down @ 4:30 (AM) (PM) Date 3-16-91

Cement circulated yes No. of Sacks 300

Cemented by Western Co Witnessed by JR

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: