

## FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Corinne B. Grace</u>		Lease <u>Salomeh</u>		Well # <u>1</u>	
Location of Well	Unit <u>M</u>	Section <u>36</u>	Township <u>21</u>	Range <u>30</u>	County <u>Eddy</u>
Drilling Contractor	<u>Cactus Drilg Co</u>		Type of Equipment <u>Rotary</u>		

## APPROVED CASING PROGRAM

✓ 1. Witness:

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>54.50 #</u>		<u>400</u>	<u>700 Circ</u>
<u>12 1/4</u>	<u>8 5/8</u>	<u>24 + 32 #</u>		<u>3500</u>	<u>1500 Circ</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>15.50 + 17 #</u>		<u>7600</u>	<u>1000</u>

Casing Data:

Surface            joints of 13 3/8" inch 54.50 # Grade J-55

(Approved) (Rejected)

Inspected by M.S. date 1-7-91

Cementing Program

Size of hole 17 1/2" Size of Casing 13 3/8" Sacks cement required           Type of Shoe used guide Float collar used insert Btm 3 jts welded yesTD of hole 415' Set 415' Feet of 13 3/8" inch 54.50 # Grade J-55New-used csg. @ 415' with 600 220cc sacks neat cement around shoe  
+            sax            additives           Plug down @ 2:45 (AM) (PM) PM Date 1-7-91Cement circulated yes No. of Sacks 175 exCemented by Halliburton Witnessed by Mike StubblefieldTemp. Survey ran @            (AM) (PM) Date            top cement @           Casing test @            (AM) (PM) Date           Method Used            Witnessed by           Checked for shut off @            (AM) (PM) Date           Method used            Witnessed by           Remarks:           

No centralizers or baskets