

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Corinne B. Grace</u>		Lease <u>Salomeh</u>		Well # <u>1</u>	
Location of Well	Unit <u>M</u>	Section <u>36</u>	Township <u>21</u>	Range <u>30</u>	County <u>Eddy</u>
Drilling Contractor	<u>Cactus Drilg Co</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 5/8	54.50 #		400	700 Circ
12 1/4	* 8 5/8	24 + 32 #		3500	1500 Circ
7 7/8	5 1/2	15.50 + 17 #		7600	1000

Casing Data:

Surface _____ joints of 8 5/8" inch 24-32 # Grade J-55(Approved) (Rejected)Inspected by M.S. date _____

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____Type of Shoe used guide Float collar used yes Btm 3 jts welded yesTD of hole 3500' Set 3500' Feet of 8 5/8" Inch 24-32 # Grade J-55New used csg. @ 3500' with 250 270cc sacks neat cement around shoe+ 1865 sax Hall. life C additives (10# salt - 10# gilsonite - 1/4# floccal)Plug down @ 8:30 (AM) (PM) Date 2-14-91Cement circulated No No. of Sacks - 0 -Cemented by Halliburton Witnessed by mike (Stubblefield)Temp. Survey ran @ 6:30 (AM) (PM) Date 2-15-91 top cement @ 750'

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: + 885 sx Hall. life C (10# salt, 1/4# floccal)

1. Ran 1" + Tagged toe @ 710' w/ 100 sx Cl. C. 370cc

2. Ran 1" + Tagged toe @ 805' w/ 50 sx Cl. C. 370cc. 6 yards pea gravel

3. Ran 1" + Tagged toe @ 780' w/ 100 sx Cl. C. 370cc

Lost circ. @ 672' + regained

4. Ran 1" + Tagged toe @ 579' w/ 350 sx Cl. C. -
Cement circulated to surface