## Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C.103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

CONDITIONS OF APPROVAL, IP ANY:

## OIL CONSERVATION DIVISION

P.O. Box 2088

WELL API NO.

P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mex	ico 8 <b>760457088</b>	30-015-26626	
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410	M10.0	5. Indicate Type of Lease STATE X FEE	
\	MAR 6 1991	6. State Oil & Gas Lease No. K-4474	
SUNDRY NOTICES AND REPORTS ON (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEE DIFFERENT RESERVOIR. USE "APPLICATION FOR (FORM C-101) FOR SUCH PROPOSALS.)	R PERMIT"	7. Lease Name or Unit Agreement Name	
1. Type of Well: OIL WELL  2. Name of Operator OTHER		- SALOMEH	
CORINNE B. GRACE		8. Well No.	
3. Address of Operator P.O. Box 1418 Carlsbad, New M 4. Well Location	lexico 88220	9. Pool name or Wildcat Cabin Lake Delaware	
Unit Letter M : 330' Feet From The West	Line and33	· · · · · · · · · · · · · · · · · · ·	
Section 36 Township 21 South	Range 30 East	NMPM Eddy County	
324	ther DF, RKB, RT, GR, etc.)		
Check Appropriate Box to Indica NOTICE OF INTENTION TO:			
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK	SSEQUENT REPORT OF:	
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING	ALTERING CASING	
PULL OR ALTER CASING	CASING TEST AND CI		
OTHER:	OTHER:		

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Commence drilling 12 1/4" hole at 3:45 PM 2-8-91. Lost circulation at 672'. Regain returns with LCM pills. Drill 12 1/4" hole to 3500'. TD 12 1/4" hole at 9:15 AM on 2-14-91. Rig up and run 3501' of 8 5/8" casing consisting of the following: 1038' 8 5/8" 32# J-55 ST&C Csg., 2296' of 8 5/8" 24# J-55 ST&C csg. & 165' of 8 5/8" 32# J-55 ST&C csg. Csg shoe at 3500'. Float collar at 3457'. Cement with 2750 sx Halliburton Lite + 10#/sx gilsonite + 10#/sx salt + 1/4#/sx Flocele. Yield 2.2 cu/ft per sx. Wt.--12.4#/gal. Tail with 250 sx. Class "C" + 2% CaCl2. (Yield 1.32 cu/ft per sx. Wt:--14.8#/gal. Did not circulate cement. Plug down at 8:30 PM 2-14-91. Run temp. survey at 6:30 AM 2-15-91 and showed top of cement at 742'. Cement annulus with 600 sx. Class "C" + 2% CaCl2 in 4 stages through 1" kobe tubing. Curculated cement to surface at 12:30 AM 12-16-91. NMOCD--Mike Stubblefield witnessed. Wait on cement 24 hrs. Test casing and BOP to 1500# for 30 min. OK.

I hereby certify that the infe	primation shows is true and complete to the best of m	ny knowledge and belief.	
SIGNATURE	Some Tie	Agent	
TYPE OR PRINT NAME	Gene Lee		TELEPHONE NO. 622-7355
(This space for State Use)	ORIGINAL SIGNED BY		
AJIROVID BY	MIKE WILLIAMS SUPERVISOR DISTRICT II		MAR 8 1991