

RECEIVED

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

APR 20 9 52 AM '93

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

CAR AREA

1. oil ☐ well ☐ gas well ☐ other ☐
2. NAME OF OPERATOR  
Harvey E. Yates Company
3. ADDRESS OF OPERATOR  
P.O. Box 1933, Roswell, N.M. 88202
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 330' FSL & 790' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE  
Cabin Lake 34 Federal, NM-64594
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Cabin Lake 34 Federal
9. WELL NO.  
#1
10. FIELD OR WILDCAT NAME  
Cabin Lake Delaware
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 34, T21S, R30E
12. COUNTY OR PARISH  
Eddy
13. STATE  
N.M.
14. API NO.  
30-015-26631
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3192.2' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3-23-93 CIBP @ 6900' - dump 50' cement on top  
3-24-93 Spot 20 sxs @ 3650' - 3550'  
Cut & pull 2115' of 5 1/2"  
3-24-93 Spot 45 sxs @ 2165' - 1992' tagged  
3-25-93 Spot 40 sxs @ 452' - 298'  
3-25-93 Spot 15 sxs @ 50' - surface

Post 20-2  
5-14-93  
PFA

Install dry hole marker  
Circulated mud

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass TITLE Engineer DATE 4/19/93

(ORIG. SGD.) DAVID R. GLASS (This space for Federal or State Engineer)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE APR 27 1993