

c151

RECEIVED

MAY 15 1991

O.C. J. ARTESIA OFFICE

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals

5. Lease Designation and Serial No. NM 04825
6. If Indian, Allottee or Tribe Name N/A
7. If Unit or CA, Agreement Designation N/A
8. Well Name and No. Trigg AIN Federal #1
9. API Well No. 30-015-26697
10. Field and Pool, or Exploratory Area Undesignated Morrow
11. County or Parish, State Eddy, NM

SUBMIT IN TRIPLICATE

1. Type of Well [] Oil Well [X] Gas Well [] Other
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address and Telephone No. 105 South 4th St., Artesia, NM 88210 (505) 748-1471
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1980' ENL & 660' FEL, Sec. 28-20S-29E (Unit H)

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION: [] Notice of Intent, [X] Subsequent Report, [] Final Abandonment Notice
TYPE OF ACTION: [] Abandonment, [] Recompletion, [] Plugging Back, [] Casing Repair, [] Altering Casing, [] Other Surface, [] Change of Plans, [] New Construction, [] Non-Routine Fracturing, [] Water Shut-Off, [] Conversion to Injection, [] Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*
Spudded 26" hole 9:00 PM 4-29-91. Set 40' of 30" conductor. Redi-mix to surface with 2 1/2 yds. Resumed drilling 7:00 PM 5-2-91. Lost circulation at 175'. Lost float shoe in hole at 314'. Spud on fish with bit. Set cement plugs as follows: 550' sx at 352'; 400 sx at 248'; 200 sx at 240'. WOC 16 hrs. Cement w/238 sx Lite "C" + 65/35 - 6 w/10% Thixset, 5# Gilsonite, 1% CaCl and 238 sx Lite "C" + 65/35 - 6 1/2# Cellofill+2% CaCl + 450 sx "C" Neat w/2% CaCl2. PD 3:00 AM 4-8-91 with 200 psi. Did not circulate. SI with no flow. Observed by Cathy, BLM, Carlsbad, NM. WOC 4 hrs. Ran 1". Tag cement 235'. Spot 50 sx "C" Neat w/3% CaCl2. PD 8:30 AM 5-8-91. WOC 3 1/2 hrs. Ran 1". Tag cement 185'. Spot 150 sx "C" Neat w/3% CaCl2. PD 12:00 Noon 5-8-91. WOC 1 1/2 hrs. Ran 1". Tag cement 120'. Spot 375 sx "C" w/3% CaCl2. PD 1:30 PM. WOC 7 hrs. Set 50 sacks plug 30-35' w/3/8" pea gravel and 150' sack plug 30-35' with pea gravel. Circulate 20 sacks to surface. Drill out 8:30 PM 5-8-91. WOC 18 hrs. Reduced hole to 17-1/2" and resumed drilling. Note: New casing point discussed and OK'd by Jim Amos, BLM, Carlsbad, NM. Drilled original hole to 427'. Lost float shoe in hole at 314'. Drove to 353' and set cement plug back to 240' (1150 sacks 18+ ppg cement). Side track and drill to 389'. Run 20" casing and cement to surface.

14. I hereby certify that the foregoing is true and correct
Signed [Signature] Title Production Supervisor Date 5-10-91

Approved by [Signature] Title [Signature]
Conditions of approval, if any:

ACCEPTED FOR RECORD
MAY 14 1991
CARLSBAD, NEW MEXICO

18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

*See Instruction on Reverse Side