

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Primero Oper. Inc.</u>		Lease <u>UZI</u>		Well # <u>1</u>	
Location of Well	Unit <u>N</u>	Section <u>18</u>	Township <u>21</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	<u>United</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>* 13 3/8</u>	<u>54.5</u>		<u>500</u>	<u>500 Surf</u>
<u>12 1/4</u>	<u>* 8 5/8</u>	<u>24.0</u>		<u>1500</u>	<u>1000 Surf</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>15.5</u>		<u>1800</u>	<u>500</u>

Casing Data:

Surface joints of 8 7/8" inch 24 # Grade J-55(Approved) (Rejected)Inspected by M.S. date 4-12-91

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required Type of Shoe used guide Float collar used insert Btm 3 jts welded yesTD of hole 1260' Set 1260' Feet of 8 5/8" Inch 24 # Grade J-55New-used csg. @ 1260' with 300 220cc sacks neat cement around shoe
+ 400 sax Hall Life additives 10# gylconite, 1/4# flo sealPlug down @ 11:30 (AM) (PM) Date 4-14-91Cement circulated yes No. of Sacks 625xCemented by Halliburton Witnessed by Mike StubblefieldTemp. Survey ran @ (AM) (PM) Date top cement @ Casing test @ (AM) (PM) Date Method Used Witnessed by Checked for shut off @ (AM) (PM) Date Method used Witnessed by Remarks:

Base Reef - 1166'

Well returns to TD