

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	<input checked="" type="checkbox"/>
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED

APR 26 1991

5a. Indicate Type of Lease  
State ☐ Pool ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name  
UZI

9. Well No.  
1

10. Field and Pool, or Wildcat  
WILDCAT, DELAWARE

12. County  
EDDY

SUNDRY NOTICES AND REPORTS ON WELLS O. C. D.  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO AN ABANDONED WELL OR TO RE-ENTER AN ABANDONED WELL. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator  
PRIMERO OPERATING, INC.

3. Address of Operator  
P.O. BOX 1433, ROSWELL, NM 88202-1433

4. Location of Well  
UNIT LETTER N 2310 FEET FROM THE WEST LINE AND 330 FEET FROM THE SOUTH LINE, SECTION 18 TOWNSHIP 21S RANGE 25E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)  
3451 KB

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

W.O.C. 24 1/2 hrs. NM BOP and test casing to 800 psi for 30 min. Casing held okay. Commenced drilling 7 7/8" hole @ 11:50 pm 4/15/91. Drilled 7 7/8" hole to 3010'. Logged well w/ CNL-LDT, DLL-MSFL. Set 35 sx cement plug @ 2006' WOC 2 1/2 hrs. and tag plug @ 1930'. Ran 47 joints used 4 1/2" 10.5# K-55 pipe w/ insert float Texas Pattern Shoe & 5 centralizers in hole and landed @ 1930'. Cemented casing w/ 35 sx Class C w/ 2% CaCl and 170 sx class C w/ 6# salt per sack and 2%, CFR3. Plug down @ 7 pm 4/22/91. Est. top of cement @ 988'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE PRESIDENT

DATE 4/25/91

APPROVED BY THEOPH WHITE IV  
ORIGINAL SIGNED BY  
MIKE WILLIAMS  
SUPERVISOR, DISTRICT II

TITLE

DATE APR 30 1991

CONDITIONS OF APPROVAL