

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DEC 10 1991

O. C. D.

WELL API NO.
30-015-26715

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V-1673

7. Lease Name or Unit Agreement Name

Lost Tank AIS State

8. Well No.
4

9. Pool name or Wildcat
Lost Tank Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The West Line

Section 36 Township 21S Range 31E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3572' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Intermediate Casing ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11" hole 5:15 PM 11-28-91. Ran 102 jts 85-/8" 32# HC-80 and J-55 LT&C and ST&C casing set 4175'. Float shoe set 4175', float collar set 4136'. DV tool set 2850'. Cmt'd in two stages as follows: Stage I - 425 sx "C" + 10#/sx Salt + 10#/sx Gilsonite + .3% CF-14 (yield 1.32, wt 14.8). Tail in w/200 sx "C" + 1% CaCl2 (yield 1.32, wt 14.8). PD 6:35 AM 11-29-91. Circulated 170 sacks. Circulated thru DV tool 4 hours. Stage II - 1500 sx PSI "C" + 10#/sx Salt + 10#/sx Gilsonite (yield 1.99, wt 12.9). Tail in w/100 sx "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 11:35 AM 11-29-91. Bumped plug to 2500 psi, released pressure and float held okay. Circulated 350 sacks. WOC. Drilled out 1:30 PM 11-30-91. WOC 30 hrs and 55 mins. NU and tested to 1000 psi for 15 minuts, OK. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 12-6-91

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

APPROVED BY CHIEF OF DIVISION TITLE CHIEF OF DIVISION DATE DEC 13 1991

CONDITIONS OF APPROVAL, IF ANY: