

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Chi Oper. Inc.</u>		Lease <u>Wiser ST</u>		Well # <u>3</u>	
Location of Well	Unit <u>E</u>	Section <u>9</u>	Township <u>21</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>L. M. rig #2</u>		Type of Equipment		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2"</u>	<u>13 3/8"</u>	<u>48#</u>		<u>350'</u>	<u>circ.</u>
<u>12 1/4"</u>	<u>8 5/8"</u>	<u>24#</u>		<u>2050'</u>	<u>..</u>
<u>7 7/8"</u>	<u>5 1/2"</u>	<u>15.50#</u>		<u>4400'</u>	<u>700'</u>

Casing Data:

Surface _____ joints of 8 5/8" inch 24 # Grade J-55
(Approved) (Rejected)

Inspected by m.c. date 4-30-91

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____

Type of Shoe used guide Float collar used yes Btm 3 jts welded yes

TD of hole 2150' Set 2150' Feet of 8 5/8" inch 24 # Grade J-55

New used csg. @ 2150' with 100 270cc sacks neat cement around shoe
+ 790 sax CI C. Lite additives 470 gel, 10 # thirst

Plug down @ 11:00 (AM) (PM) Date 5-6-91

Cement circulated No No. of Sacks - 0 -

Cemented by Western Company Witnessed by Mike Stubblefield

Temp. Survey ran @ 5:00 (AM) (PM) Date 5-6-91 top cement @ 420' *

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

* 1" on reverse side Lost circ. @ 420'

1. tag @ 440' w/25 sx cl c 370cc
2. tag @ 430' w/25 sx cl c 370cc
3. tag @ 430' w/25 sx cl c 370cc
4. tag @ 430' w/25 sx cl c 370cc - gravel
5. tag @ 430' w/25 sx cl c 370cc - gravel
6. tag @ 430' w/25 sx cl c 370cc - gravel
7. tag @ 430' w/25 sx cl c 370cc - gravel
8. tag @ 429' w/25 sx cl c 370cc - gravel
9. tag @ 429' w/75 sx cl c 370cc - gravel
- 10 tag @ 175' w/65 sx cl c 370cc (Total 17 yards gravel)