

Submit 3 Copies To Appropriate District Office

District I
1625 N. French Dr., Hobbs, NM 87240

District II
811 South First, Artesia, NM 87210

District III
1000 Rio Brazos Rd., Aztec, NM 87410

District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-26725

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

L-7010

7. Lease Name or Unit Agreement Name

Wiser State

8. Well No.

3

9. Pool name or Wildcat

Catchlaw Draw, East (Delaware)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Devon Energy Production Co., L P /

3. Address of Operator

20 N. Broadway, Suite 1500, Oklahoma City, OK 73102-8260

4. Well Location

Unit Letter E 2,257 feet from the North line and 862 feet from the West line

Section 9

Township 21S

Range 26E

NMPM

County Eddy

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

GR=3,223' RKB=3,232'

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOBS ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work). SEE RULE 1103. For Multiple Completions: Attach diagram of proposed completion or recompletion.

Plugged And Abandon As Follows:

08/22/02 - Cap existing CIBP at 2,775' with 25 sxs cement.

Circulate wellbore full with 9.5ppg mud.

Spot balanced cement plug 2,225' with 25 sxs. WOC. Tagged top of plug at 1,945'.

Perforate 5 1/2" casing at 400' with 4 shots.

Pump 150 sxs cement down 5 1/2" casing. Circulated cement to surface in 5 1/2" and 8 5/8" annulus.

08/29/02 - Cut off casing 3' below surface, capped off casing with 5 sxs (cement had dropped 10' in annulus).

Install dry hole marker and clean up location.

Note: 1. Cement was Class "C" at 14.8ppg with a yield of 1.32 cu ft/sx.

2. Salt Section: Top at 100' Base at 340'

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Charles H. Carleton

TITLE Senior Engineering Technician

DATE 09/05/2002

Type or print name Charles H. Carleton

Telephone No. (405)552-4528

(This space for State use)

APPROVED BY

[Signature]

TITLE

DATE OCT 29 2002

Conditions of approval, if any: