

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

JUL 18 1991

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS
ARTESIA, OFFICE

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION /

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit I, 330' FEL & 1980' FSL, Sec. 25-T21S-R31E, NMPM

5. Lease Designation and Serial No.

NM 61358

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Wolf AJA Federal #4

9. API Well No.

30-015-26777

10. Field and Pool, or Exploratory Area

Undes. Livingston Ridge Delaware

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud, Surface

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 26" hole 6:45 PM 7-4-91 with rathole. Notified Cathy, BLM, Carlsbad, NM, of spud. Set 40' of 20" conductor and ready-mix to surface with 4-1/2 yards. Ran 20 joints 13-3/8" 54.5# J-55 ST&C casing set 850'. Guide shoe set 850', insert float set 809'. Cemented w/ 500 sx Pacesetter Lite w/1/4# Celloseal + 10# salt (yield 1.79, wt 12.8). Tailed in w/250 sx "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 10:30 PM 7-6-91. Bumped plug to 700 psi, float held OK. Circulated 139 sacks cement. WOC. Drilled ut 8:30 PM 7-7-91. WOC 22 hrs. NU and tested to 500 psi for 30 minutes. Reduced hole to 12 1/4" and resumed drilling. Witnessed by Cathy, BLM, Carlsbad, NM.

14. I hereby certify that the foregoing is true and correct

Signed [Signature]


Title Production Supervisor

Date 7-11-91

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____



Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side