

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

clsr
dp

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-26794

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V-1673

7. Lease Name or Unit Agreement Name

Lost Tank AIS State

8. Well No.
8

9. Pool name or Wildcat
Lost Tank Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter P : 660 Feet From The South Line and 660 Feet From The East Line
Section 36 Township 21S Range 31E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3591' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 8:35 AM 10-2-91 with rathole. Set 40' of 20" conductor; cement to surface with redi-mix. Notified Betty Rollins, NMOCD, Artesia, NM of spud. Resumed drilling 17 1/2" hole 1:00 PM 10-3-91. Ran 21 joints 13-3/8" 54.5# J-55 ST&C casing set 875'. Guide shoe set 875', insert float set 835'. Cmt'd w/500 sx PSL "C" + 2% CaCl2 + 1/4#/sx Celloseal (yield 1.76, wt 12.9). Tailed in w/250 sx "C" + 2% CaCl2 + 1/4#/sx Cellsoeal (yield 1.32, wt 14.8). PD 9:30 PM 10-4-91. Bumped plug to 600 psi, released pressure, float held okay. Circ. 100 sacks. WOC. Drilled out 5:30 PM 10-5-91. WOC 20 hrs. NU and tested to 500 psi for 30 minutes. Reduced hole to 11'. Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Juanita Goodlett

TITLE Production Supervisor

DATE 10-8-91

TELEPHONE NO. 505/748-1471

TYPE OR PRINT NAME

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

OCT 11 1991

CONDITIONS OF APPROVAL, IF ANY: