

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

RECEIVED

OCT 11 1991

WELL API NO. 30-015-26794
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-1673
7. Lease Name or Unit Agreement Name Lost Tank AIS State
8. Well No. 8
9. Pool name or Wildcat Lost Tank Delaware

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG AND ABANDON A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION	3. Address of Operator 105 South 4th St., Artesia, NM 88210
4. Well Location Unit Letter P : 660 Feet From The South Line and 660 Feet From The East Line Section 36 Township 21S Range 31E NMPM Eddy County		
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3591' GR		

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Set 8-5/8" casing <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11" hole 10-11-91. Ran 109 joints 8-5/8" 32# HC-80 and J-55 casing set 4500'. Float shoe set 4500', float collar set 4459'. Cemented w/1500 sx PSL "C" w/1/4#/sx Celloseal, 10#/sx Salt, 5#/sx Gilsonite (yield 1.94, wt 12.9). Tailed in w/200 sx "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 8:20 PM 10-11-91. Bumped plug to 1900 psi, float held okay. Cement circulated 250 sacks. WOC. Drilled out 2:45 PM 10-12-91. WOC 18 hrs and 25 mins. NU and tested to 1000 psi for 15 mins, OK. Reduced hole to 7-7/8", resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 10-15-91  
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT II

CONDITIONS OF APPROVAL, IF ANY:

OCT 29 1991