

SURFACE USE PROGRAM

SMITH FEDERAL GAS COM NO. 2 - Cont'd PAGE 2

6) Construction Materials:

- A) Construction materials will be obtained from the drill site's excavation. If additional material is needed, it will be purchased from a local source and transported the site over the access route as shown in Exhibit "B".

7) Methods for Handling Waste Disposal:

- A) Drill cuttings will be disposed of in the reserve pit.
- B) Trash, waste paper, garbage, and junk will be placed in a portable trash container. The container will be covered to prevent scattering by the wind. All material will be properly disposed of at a licensed dump site upon completion of the well.
- C) Sewage from trailer houses and portable johns will be hauled off by a licensed sewage disposal company.
- D) After the completion of the well, drilling fluids will be allowed to evaporate in the reserve pit until the pit is dry enough for back filling. If the drilling fluids do not evaporate in a reasonable period of time, they will be picked up by truck and transported to a State approved disposal site.
- E) Excess mud chemicals, including broken sacks, will be picked up by the supplier.

8) Ancillary Facilities:

- A) None required.

9) Well Site Layout:

- A) Exhibit "E" shows the maximum dimensions of the proposed well site layout. The drilling contract has not yet been selected, but the pad will be no larger than shown.
- B) The reserve pit will be lined with PVC or Polyethylene liner. The pit liner will be 6 mils thick and will extend a minimum of 2' over the reserve pit dikes where the liner will be anchored down.