

B. The estimated tops of geologic markers are as follows:

Bell Canyon	1900'	Strawn	10,280'
Cherry Canyon	2650'	Atoka	10,540'
Bone Spring	5060'	Morrow	11,200'
Wolfcamp	8600'		

C. The estimated depths at which anticipated water, oil or gas are expected to be encountered:

Water: Possible surface water between 100-300'.

Oil: N/A

Gas: Deleware @ 4300'

Strawn @ 10,300-10,400'

Atoka @ 10,640-10,680'

Morrow @ 11,200-11,600'

D. Proposed Casing Program: See Form 9-331C.

E. Pressure Control Equipment: See Form 9-331C and Exhibit "D".

F. Mud Program: See Form 9-331C.

G. Auxiliary Equipment: Rotating head, PVT system, and Mud Gas Separator.

H. Testing and Coring Program: One DST is anticipated at this time in the Strawn from 10,300-10,400'.
No cores are planned at the present.

Logging: Gamma Ray - Spectral
Density - Dual Spaced Neutron Log; TD to surface
Gamma Ray - Dual Laterolog
Microguard Log - TD to Intermediate casing.

I. No abnormal pressures or temperatures are anticipated. In the event abnormal pressures are encountered the proposed mud program will be modified to increase the weight.

J. Anticipated Starting Date: As soon as possible after BLM approval.

10. OTHER INFORMATION:

The geologic surface formation consists of hard clay interspersed with sand and chert outcroppings. Vegetative cover is generally sparse and consist mostly of greasewood and bear grass.