

APR - 6 1992

Form C-103  
Revised 1-1-89+ clsf  
dpSubmit 3 Copies  
to Appropriate  
District OfficeState of New Mexico  
Energy, Minerals and Natural Resources Department

O. C. D.

## OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.

30-015-26906

5. Indicate Type of Lease

STATE ☒FEE ☐6. State Oil & Gas Lease No.  
L 5036

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Glider AKG State

1. Type of Well:

OIL  
WELL ☐GAS  
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

8. Well No.

1

3. Address of Operator

105 South 4th St., Artesia, NM 88210

9. Pool name or Wildcat

Burton Flat Morrow

4. Well Location

Unit Letter F : 1980 Feet From The North Line and 1980 Feet From The West LineSection 17 Township 21S Range 27E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3204' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

## SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐REMEDIAL WORK ☐ALTERING CASING ☐TEMPORARILY ABANDON ☐CHANGE PLANS ☐COMMENCE DRILLING OPNS. ☒PLUG AND ABANDONMENT ☐PULL OR ALTER CASING ☐CASING TEST AND CEMENT JOB ☒OTHER: ☐OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole, 8:35 AM 3-25-92. Set 40' of 20" conductor and cemented to surface with redi-mix. Notified NMOCD - Artesia, NM of spud. Resumed drilling 17½" hole 11:15 AM 3-28-92. Ran 14 joints 13-3/8" 54.5# J-55 casing set 602'. Guide shoe set 602'. Insert float set 559'. Cemented w/630 sx "C" + 2% caCl2 (yield 1.32, wt 14.8). PD 6:26 AM 3-29-92. Bumped plug to 700 psi, float held okay. Circulated 75 sacks cement. WOC. Drilled out 2:30 AM 3-30-92. WOC 20 hrs. NU and tested to 500 psi for 15 minutes. Reduced hole to 12½" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Production Supervisor

DATE

TYPE OR PRINT NAME

Juanita GoodlettTELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APR 10 1992

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: