

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

MAR 11 1992

O. C. D.

WELL API NO.

30-015-26916

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter AI : 990 Feet From The North Line and 660 Feet From The East Line

Section 35

Township

20 1/2-S

Range

23-E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3700' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 11:40 AM 3-1-92. Set 40' of 20" conductor. Redmixed to surface w/4 yds. Resumed drilling 14-3/4" hole 8:15 AM 3-4-92. TD 14-3/4" hole 3-6-92. Ran 23 joints 9-5/8" 36# J-55 ST&C casing set at 1005'. Guide shoe set 1005', insert float set 960'. Cmt'd w/ 150 sx "H" w/12% Calseal + 1/2# Flocele + 10# Gilsonite + 2% gel w/2% CaCl2 (yield 1.7, wt 14.2) followed by 600 sx Howco Lite w/1/2# Flocele + 10# Gilsonite w/2% CaCl2 (yield 1.9, wt 12.4). Tailed in w/200 sx "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 6:00 AM 3-7-92. Bumped plug to 750 psi, float held okay. Cement did not circulate. Tagged TOC at approx. 115' with tape. Redi-mix to surface with 6 yards redi-mix. WOC. Drilled out 3:15 AM 3-8-92. WOC 21 hrs and 15 minutes. NU and tested to 3000psi for 10 minutes. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Juanita Goodlett

TITLE Production Supervisor

DATE 3-10-92

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

MAR 13 1992

CONDITIONS OF APPROVAL, IF ANY: