Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

KELEIVED

MIL 1 3. 1=92

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 0473817 6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. Well Gas Well Chamois AKE Fed. Com #1 2. Name of Operator 9. API Well No. YATES PETROLEUM CORPORATION V (505) 748-1471)30-015-26923 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area 105 South 4th St., Artesia, NM 88210 Undesignated Morrow 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State Unit G, 1980' FNL & 1980' FEL, Sec. 33-T20S-R29E Eddy, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment Notice of Intent New Construction Recompletion Non-Routine Fracturing Subsequent Report Plugging Back Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice → Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 36" hole 8:00 AM 6-28-92. Set 39' of 30" conductor pipe. Redi-mix to surface. Notified BLM Answering Service, Carlsbad, NM, of spud. Resumed drilling 26" hole 12:30 PM 6-30-92. Ran 11 joints 20" 94# J-55 ST&C casing set 461'. Guide shoe set 461'. Insert float set 417'. Cemented w/500 sx PSL "C" w/1/2#/sx Celloseal, 2% CaCl2 (yield 1.99, wt 12.4). Tailed in w/400 sx "C" w/2% CaCl2 (yield 1.32,w t 14.8). PD 10:00 AM 7-1-92. Bumped plug to 400 psi, float held OK. Circulate 110 sacks cement. WOC. Drilled out 4:30 AM 7-2-92. WOC 18 hrs, 30 mins. Cut off and weld on flow nipple. Reduced hole to $17\frac{1}{2}$ " and resumed drilling. 14. I hereby certify that the foregoing is true and correct Title Production Supervisor andlett Date space for Federal or State office use) Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements

or representations as to any matter within its jurisdiction.