

CLSF
Op

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, H-400, NM 88240

DISTRICT II
P.O. Drawer DD, Aztec, NM 88210

DISTRICT III
1000 E. Duran Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

JUN 22 1992

O. C. D.

WELL API NO.
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. V. 737
7. Lease Name or Unit Agreement Name A. E. 36 State
8. Well No. 1
9. Pool name or Wildcat Avalon, E.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well OIL ☐ GAS ☒ OTHER
2. Name of Operator Collins & Ware, Inc.
3. Address of Operator 303 W. Wall, Suite 2200, Midland, Texas 79701
4. Well Location Unit Letter <u>E</u> : <u>2180</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>West</u> Line Section <u>36</u> Township <u>205</u> Range <u>28 E</u> NMPM <u>Eddy</u> County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3207.6 G.L.

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
PLUG AND ABANDON ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPNS. ☐
CHANGE PLANS ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOB ☒
OTHER: ☐	OTHER: Spud, Surface casing 20" ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Zia Drill Rig No. 7 spudded a twenty-six inch hole on June 5, 1992. The twenty-six inch hole was drilled to a depth of 354' K.B. Twenty inch 94#/ft., K-55, ST&C casing was run and set at 357.26' K.B. Cemented with 660 sacks Premium Plus cement with 2% CACL₂, 1/4# floccle/sk., (1.32 cu.ft./sk. yield, 14.8#/gallon). Tailed in with 50 sacks Premium Plus cement (1.32 cu.ft./sk. yield, 14.8#/gallon). Plug down at 10:00 PM June 5, 1992. Circulated 85 sacks cement to surface. Waited on cement 25.75 hours. Tested casing and BOP to 1600 psig, held O.K. second test. Job witnessed by Mike Stubbiefield with the NMCED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE James F. O'Brian TITLE Agent for Collins & Ware, Inc. DATE 6/16/92
FULL OR TRUE NAME James F. O'Brian TELEPHONE NO.

(This space for State Use)

APPROVED BY Mike Williams TITLE DATE

JUN 29 1992